



Gigabit Ethernet Network Adapter

EN-9230TX-32

32-bit, 66/33MHz PCI 10/100/1000Mbps UTP

Features

- Comply with the IEEE 802.3, IEEE 802.3u, IEEE 802.3ab and IEEE 802.3x.
- Supports 32-bit, 66/33MHz PCI Local Bus Master for high speed operation of Rev. 2.2/2.1 specification.
- One RJ-45 connector supports 1000Mbps, 100Mbps or 10Mbps network speed and Auto-MDI/MDI-X.
- Plug-and-Play installation--auto-setup IRQ and I/O address.
- Supports IEEE 802.3x full-duplex flow control.
- Full-duplex design to double the performance to 20/200/2000Mbps.
- Supports PCI 2.2 Wake On LAN function.
- Supports IEEE 802.1Q VLAN tagging.
- Supports Jumbo Frame.
- Supports Web-based Management.

Specifications

Product	EN-9230TX-32
Chipset	Realtek RTL8169S-32 Single Chip
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x
Bus Architecture	PCI V2.2/2.1, 32-bit, 66/33MHz
Network Power	UTP x 1 (Auto-MDI/MDI-X)
Network Drivers	Windows 98/98SE/Me/NT/2000/XP/Server 2003, Netware Server 4.x/5.x/6.x, Netware ODI for DOS, Unix and Linux
LED	Link/Activity
Dimension	120 x 40 mm (4.72 x 1.77 in.)
Temperature	32~113°F (0~45°C)
Humidity	10-95% (NonCondensing)
Certification	FCC Class B, CE Mark, C-Tick, VCCI

Taiwan / Headquarters
Edimax Technology Co., Ltd.
TEL : 886-2-2299-9648
FAX : 886-2-2299-5647
sales@edimax.com.tw

China
Beijing Edimax Science &
Technology Co., Ltd.
TEL : 8610-6213-9288
FAX : 8610-6213-9231
sales@edimax.com.cn

U.S.A.
Edimax Computer Company
TEL : 1-408-496-1105
FAX : 1-408-980-1530
sales@edimax.com

Latin America
TEL : 1-786-845-8099
FAX : 1-786-331-8490
sales_latinamerica@edimax.com

Europe
TEL : 31-499-377344
FAX : 31-499-372647
sales@edimax.nl

U.K.
Edimax Technology (UK) Ltd.
TEL : 44-0-1908-255901
FAX : 44-0-1908-255700
info@edimax.co.uk

